

Discovering the Skyline of Web Databases

Abolfazl Asudeh[‡], Saravanan Thirumuruganathan[‡], Nan Zhang^{††}, Gautam Das[‡]

[‡]University of Texas at Arlington; ^{††}George Washington University

[‡]{ab.asudeh@mavs, saravanan.thirumuruganathan@mavs, gdas@cse}.uta.edu,
^{††}nzhang10@gwu.edu

ABSTRACT

Many web databases are “hidden” behind proprietary search interfaces that enforce the top- k output constraint, i.e., each query returns at most k of all matching tuples, preferentially selected and returned according to a proprietary ranking function. In this paper, we initiate research into the novel problem of skyline discovery over top- k hidden web databases. Since skyline tuples provide critical insights into the database and include the top-ranked tuple for every possible ranking function following the monotonic order of attribute values, skyline discovery from a hidden web database can enable a wide variety of innovative third-party applications over one or multiple web databases. Our research in the paper shows that the critical factor affecting the cost of skyline discovery is the type of search interface controls provided by the website. As such, we develop efficient algorithms for three most popular types, i.e., one-ended range, free range and point predicates, and then combine them to support web databases that feature a mixture of these types. Rigorous theoretical analysis and extensive real-world on-line and offline experiments demonstrate the effectiveness of our proposed techniques and their superiority over baseline solutions.

1. INTRODUCTION

Problem Motivation: Skyline for structured databases has been extensively studied in recent years. Consider a database with n tuples over m numerical/ordinal attributes, each featuring a domain that has a preferential order for certain applications, e.g., price (smaller the better), model year (newer the better), etc. A tuple t is said to *dominate* a tuple u if for every attribute A_i , the value of $t[A_i]$ is preferred over $u[A_i]$. The skyline is the set of all tuples t_i such that t_i is not dominated by any other tuple in the database.

Skyline is important for multi-criteria decision making, and is further related to well-known problems such as convex hulls, top- k queries and nearest neighbor search. For example, a precomputed skyline can serve as an index for efficiently answering any top-1 query with a monotonic ranking function over attributes. The extension of a skyline to a K -sky band (containing all tuples not dominated by more than $K - 1$ others) enables efficient answering of top- k queries when $k \leq K$. For a summary of research on skyline computation and their applications, please refer to Section 8.

This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/4.0/>. For any use beyond those covered by this license, obtain permission by emailing info@vldb.org.

Proceedings of the VLDB Endowment, Vol. 9, No. 7
Copyright 2016 VLDB Endowment 2150-8097/16/03.

Much of the prior work assumes a traditional database with full SQL support [5, 7, 14, 24] or databases that expose a ranked list of all tuples according to a pre-known ranking function [4, 18]. In this paper, we consider a novel problem of how to compute the skyline over a *deep web*, “hidden”, database that only exposes a top- k query interface. Unlike the traditional assumptions, real-world web databases place severe limits on how external users can perform searches. Typically, a user can only specify conjunctive queries with range or (single-valued) point conditions, depending on which one(s) the web interface supports, and receive at most k matching tuples, selected and sorted according to a ranking function that is often proprietary and unknown to the external user.

Discovering skyline tuples from a hidden web database enables a wide variety of third-party applications, ranging from understanding the “performance envelope” of tuples in the database to enabling uniform ranking functions over multiple web databases. For example, consider the construction of a diamond search service, that taps into web databases of several jewelry stores such as Blue Nile (by collecting data through their web search interfaces). While there are well-known preferential orders on all critical attributes of a diamond such as clarity, carat, color, cut and price, each jewelry store may design its own ranking function as a unique weighting of these attributes. On the other hand, the third-party service needs to rank all tuples from all stores consistently, and ideally support user-specified ranking functions (e.g., different weightings of the attributes) according to his/her own need. An efficient and effective way to enable this is to first discover the skyline tuples from the hidden web database of each jewelry store, and then apply a user-specified ranking function on all the retrieved data to obtain tuples most preferred by the user. One can see that, similarly, this approach can be used to enable third-party services such as flight search with user-defined ranking functions on price, duration, number of stops, etc.

Challenges: The technical challenges we face are fundamentally different from traditional skyline computation techniques, mainly because the data access model is completely different. In traditional skyline research, there is no top- k constraint on data access, so the algorithms can take advantage of either full SQL power or certain pre-existing data indices such as sequence access according to a known ranking function [4, 18]. On the other hand, as mentioned earlier, in hidden databases the data access is severely restricted. In principle, one can apply prior techniques developed to crawl the entire hidden database (e.g., using algorithms such as [23]), and then compute the skyline over a local copy of the database. However, as we shall show in the experimental results, such an approach is often impractical as crawling the entire database (as opposed to just the skyline) requires an inordinate number of search queries (i.e., web accesses). Note that many real-world web databases limit the

number of web accesses one can issue through per-IP-address or per-API-key limits.

Technical Highlights: We distinguish between several important categories of web search interfaces: whether range predicates are supported for the attributes (either one-ended, e.g. Price < 300, or two-ended, e.g., 200 < Price ≤ 300), or only single-value/point predicates (e.g., Number of Stops = 0) or a mix of them are allowed.

For the case of one-ended range queries, we develop **SQ-DB-SKY**, an iterative divide-and-conquer skyline discovery algorithm that starts by issuing broad queries (i.e., queries with few predicates), determines which queries to issue next based on the tuples received so far, and then gradually narrows them to more specific ones. For the case of two-ended range queries, we develop algorithm **RQ-DB-SKY**, which is similar to the previous algorithm, except that instead of being forced to issue overlapping queries, the algorithm is able to take advantage of the more powerful search interface and issue mutually exclusive queries to cover the search space and be able to terminate earlier.

For the case of point queries, the significantly weaker search interface introduces novel challenges in designing an efficient skyline discovery algorithm. For the special case of 2-dimensional data, we design algorithm **PQ-2D-SKY** that is *instance-optimal*, although the worst-case complexity is a complex function that depends not only on parameters such as n and S , but also on the domain sizes of the attributes. Unfortunately, the generalization to higher dimensions proves much more complicated, as shown by a negative result that no instance-optimal algorithm can exist for higher dimensions.

As such, our eventual algorithm for higher dimensions, **PQ-DB-SKY**, uses as a subroutine a revised version of the 2D algorithm that is able to discover all skyline from a “pruned” 2D subspace in an instance-optimal manner (though the overall algorithm for higher dimensions is not instance-optimal). Given the exponential nature of dividing a higher-dimensional space into 2D subspaces, the worst-case query cost of the algorithm can be quite large. However, as we shall show through real-world online experiments, the nature of these PQ attributes used in real-world hidden databases (e.g., they usually have small domains with all domain values occupied by real tuples) makes the actual performance of PQ-DB-SKY often fairly efficient in practice. Finally, we develop algorithm **MQ-DB-SKY** to handle hidden databases that feature a mixture of range and point attributes. All our algorithms have been extensively evaluated against multiple real-world datasets such as Yahoo! Autos, Google Flights, and Blue Nile.

2. PRELIMINARIES

2.1 Model of Hidden Database

Database: Consider a hidden web database D with n tuples over m attributes A_1, \dots, A_m . Let the domain of A_i be $Dom(A_i)$ and the value of A_i for tuple t be $t[A_i] \in Dom(A_i) \cup \{\text{NULL}\}$.

Skyline: The m attributes of a web database can be divided into two categories: *ranking attributes* with an inherent preferential order (either numeric or ordinal); and *filtering attributes* whose values are not ordered. The skyline definition only concerns the ranking attributes. For a ranking attribute A_i , we denote the total order by $<$, i.e., v_i ranks *higher* than v_j if $v_i < v_j$. With this notation, a tuple $t \in D$ is a skyline tuple if and only if there does not exist any other tuple $t' \in D$ with $t' \neq t$ such that t' dominates t , i.e. $t'[A_i] \leq t[A_i]$ for each and every ranking attribute A_i . No other tuple t' in the database outranks t on every ranking attribute.

Note that the skyline definition can be easily extended to *sky band* - i.e., a tuple is in the K -skyband if and only if it is not dominated by more than $K - 1$ tuples. One can see that the skyline

is indeed a special case of (top-1) sky band. In most parts of the paper, we focus on the problem of skyline discovery. Please refer to [2] for the extension to discovering the K -skyband ($K > 1$).

Query Interface: The web interface of a hidden database takes as input a user-specified query (supported by the interface) and produces as output at most k tuples matching the query. At the input side, the interface generally supports conjunctive queries on one or more attributes. The *predicate* supported for each attribute, however, is a subtle issue that depends on the type of the attribute and the interface design. While filtering attributes with categorical values generally support equality ($=$) only, a ranking attribute may support any subset of $<$, $=$, $>$, \leq , and \geq predicates. Since the supported predicate types turn out to be critical for our algorithm design, we leave it for detailed discussions in the next subsection.

Output-wise, the query answer is subject to the top- k constraint, i.e., when more than k tuples match the input query, instead of returning all matching tuples, the hidden database preferentially selects k of them according to a *ranking function* and returns only these top- k tuples through the interface. In this case, we say that query q *overflows* and triggers the top- k limitation. In this paper, we support a very broad set of ranking functions with only one requirement: *domination-consistent*, i.e., if a tuple t dominates t' and both match a query q , then t should be ranked higher than t' in the answer. All results in the paper hold on any arbitrary ranking function so long as it satisfies this requirement.

Filtering Attributes: While a web database may contain orderless filtering attributes, they have no bearing on the definition of skyline tuples. We further note that filtering attributes have no implication on skyline discovery *unless* there are skyline tuples with the exact same value combination on all ranking attributes. Even in this case, what one needs to do is to simply issue, for each discovered skyline tuple, a conjunctive query with equality conditions on all ranking attributes. If the query overflows, one can then crawl all tuples matching the query using the techniques in [23]. Since such a case is unlikely to happen, we make the general positioning assumption, i.e., all skyline tuples have unique value combinations on ranking attributes, as assumed in most prior work [5, 7, 14, 24]. Our experiments in § 7, however, do involve filtering attributes and confirm that they have no implication on skyline discovery.

2.2 Taxonomy of Attribute Search Interface

We now discuss in detail what types of predicates may be supported for an attribute - an issue that, somewhat surprisingly, turns out crucial for the efficiency of skyline discovery. Specifically, we partition the support into three categories depending on two factors: (1) whether range predicates are supported for the attribute, or only equality (i.e., point) predicates are allowed, and (2) when range predicates are supported, whether the range is one-ended (i.e., “better than” a user-specified value), or two-ended.

- **SQ**, i.e., *Single-ended range Query predicate*, means that predicate on A_i can be $A_i < v$, $A_i \leq v$ or $A_i = v$, where $v \in Dom(A_i)$. Note that we do not further distinguish whether $<$ or \leq (or both) is supported, because they are easily reducible to each other - e.g., one can combine the answers to $A_i < v$ and $A_i = v$ to produce that for $A_i \leq v$. On the other hand, if $A_i \leq v$ is supported but not $A_i < v$, one can take the next smaller value (than v) in $Dom(A_i)$, say v' , and then query $A_i \leq v'$ instead¹

¹Of course, in the case where $Dom(A_i)$ is an infinite set, e.g., when A_i is continuous, a tacit assumption here is that we know a small value ϵ such that no tuple can have $A_i \in (v - \epsilon, v)$. Given that the values represented in a database are anyway discrete in nature, this assumption can be easily satisfied by assuming a fixed precision level for the skyline definition.

- RQ, i.e., *Range Query predicate*, means that predicate on A_i can be $A_i < (\text{or } \leq) v$, $A_i = v$ or $A_i > (\text{or } \geq) v$.
- PQ, i.e., *Point Query predicate*, means that predicate on A_i can only be of the form $A_i = v$.

SQ vs RQ: One might wonder why both single-ended SQ and two-ended RQ exist in a web interface. To understand why, consider two examples: the *memory size* and *price* of a laptop, respectively. Both have an inherent order: the larger the memory size or the lower the price, the better. Nonetheless, their presentations in the search interface are often different:

Memory size is often presented as SQ, because there is little motivation for a user to specify an upper bound on the memory size. Price, on the other hand, is quite different. Specifically, it is usually set as an RQ attribute with two-ended range support because, even though almost all users prefer a lower price (for the same product), many users indeed specify both ends of a price range to *filter* the search results to the items they desire. The underlying reason here is that price is often correlated (or perceived to be correlated) with the quality or performance of a laptop. For the lack of understanding of the more “technical” attributes, or for the simplicity of considering only one factor, many users set a lower bound on price to filter out low-performance laptops that do not meet their needs.

SQ/RQ vs PQ: Note that range-predicate support (SQ or RQ) is strictly “stronger” than PQ: While it is easy to specify a range predicate that is equivalent to a point one, to “simulate” a range query, one might have to issue numerous point queries, especially when the domain sizes and the number of attributes are large.

Fortunately though, real-world hidden databases often only represent an ordinal ranking attribute as PQ when it has (or is discretized to) a very small domain size. For example, flight search websites set the number of stops as PQ because it usually takes only 3 values: 0, 1, or 2+. On the other hand, price is rarely PQ given the wide range of values it can take.

2.3 Problem Definition

Performance Measure: In most parts of the paper, we consider the objective of discovering *all* skyline tuples from the hidden web database. Interestingly, our solutions also feature the *anytime* property [1] which enables them to quickly discover a large portion of the skyline (see technical report [2] for details of this feature).

When our goal is complete skyline discovery, what we need to optimize is a single target: efficiency. We note the most important efficiency measure here is *not* the computational time, but *the number of queries we must issue* to the underlying web database. The rationale here is the query rate limitation enforced by almost all web databases - in terms of the number of queries allowed from an IP address or a user account per day. For example, Google Flight Search API allows only 50 free queries per user per day.

SKYLINE DISCOVERY PROBLEM: Given a hidden database D with query interface supporting a mixture of SQ, RQ or PQ for ranking attributes, without knowledge of the ranking function (except that it is domination-consistent as defined above), retrieve all skyline tuples while minimizing the number of queries issued through the interface.

3. SKYLINE DISCOVERY FOR SQ-DB

THEOREM 1. *Considering the SQ interface, there exists a database D such that discovering its skyline requires at least $O(|S|^m)$ queries.*

Due to lack of space, the proof for the lower bound of the problem complexity can be found in our technical report [2].

3.1 Key Idea: Algorithm SQ-DB-SKY

We start by considering web databases with only SQ. Our SQ-DB-SKY algorithm is an iterative divide-and-conquer one that starts by issuing broad queries, determines which queries to issue next based on the tuples received so far, and then gradually narrowing them to more specific ones. For the ease of understanding, consider the example of a 3-dimensional database. Suppose the tuple returned by $q_1 : \text{SELECT } * \text{ FROM } D$ is t_1 . Algorithm SQ-DB-SKY first issues the following three queries:

```
q2: SELECT * FROM D WHERE A1 < t1[A1]
q3: SELECT * FROM D WHERE A2 < t1[A2]
q4: SELECT * FROM D WHERE A3 < t1[A3]
```

A key observation here is that the *comprehensiveness* of skyline discovery is maintained when we divide the problem to the subspaces defined by q_2, q_3, q_4 . Specifically, every skyline tuple (besides t_1) must satisfy at least one of q_2, q_3, q_4 because otherwise it would be dominated by t_1 . Now suppose q_2 returns t_2 as top-1 (which must be on the skyline because no tuple with $A_i \geq v$ can dominate one with $A_i < v$). We continue with further “dividing” (the subspace defined by) q_2 into three queries according to t_2 :

```
q5: WHERE A1 < t2[A1]
q6: WHERE A1 < t1[A1] AND A2 < t2[A2]
q7: WHERE A1 < t1[A1] AND A3 < t2[A3]
```

Again, any skyline tuple that satisfies q_2 (i.e., with $A_1 < t_1[A_1]$) must match at least one of the three queries. One can see that this process can be repeated recursively from here: Every time a query q_j returns a tuple t , we generate m queries by appending $A_1 < t[A_1], \dots, A_m < t[A_m]$ to q_j , respectively. A critical observation here is that any skyline tuple matching q_j must match at least one of the m generated queries, because it has to surpass t on at least one attribute in order to be on the skyline. As such, so long as we follow the process to traverse a “query tree” as shown in Figure 1, we are guaranteed to discover all skyline tuples.

THEOREM 2. *Algorithm SQ-DB-SKY is guaranteed to discover all skyline tuples.*

PROOF. Consider any skyline tuple t . To prove that t will always be discovered by SQ-DB-SKY, we construct the proof by contradiction. Suppose that t is not discovered, i.e., it is not returned by any node in the tree. We start by considering the m branches of the root node. Since t is a skyline tuple, it must satisfy at least one of these branches, as otherwise it would be dominated by the tuple returned by the root node (contradicting the assumption that t is a skyline tuple). When there are multiple branches matching t , choose one branch arbitrarily. Consider the node corresponding to the branch, say $q_i : A_i < t_1[A_i]$. Since q_i matches t yet does not return it (because otherwise t would have been discovered), it must overflow and therefore have m branches of its own.

Once again, t has to satisfy at least one of these m branches (of q_i), as otherwise t would have been dominated by the tuple returned by q_i (contradicting the skyline assumption). Repeat this process recursively; and one can see that there must exist a path from the root to a leaf node in the tree, such that t satisfies each and every node on the path. Since every leaf node of the tree is a valid or underflowing query, this means that the leaf node must return t , contradicting the assumption that t is not discovered. This proves the completeness of skyline discovery by SQ-DB-SKY. \square

In order to better understand the correctness of the algorithm, consider the dummy example provided in Figure 2, and its corresponding SQ-DB-SKY tree in Figure 3. One can see that each skyline tuple appears in at least one of the branches, as otherwise it would have been dominated by another (skyline) tuple.

Algorithm 1 depicts the pseudo code for SQ-DB-SKY. Note from the algorithm that a larger k (as in top- k returned by the database) reduces query cost for two reasons: First, every returned tuple that is not dominated by another in the top- k is guaranteed to be a skyline tuple. Second, a larger k also makes the tree shallower because a node becomes leaf if it returns fewer than k tuples. This phenomenon is verified in our experimental studies.

We would like to clarify that, it is *not* needed to find the largest domain value of A_i smaller than v . Instead, so long as we find $v' < v$ such that replacing the predicate $A_i \leq v$ with $A_i \leq v'$ still leads to a non-empty query answer, the algorithms will work. The only case where we may have trouble with a \leq interface is when $A_i \leq v$ overflows, yet it takes a larger number of queries to perform binary search to find $v' < v$ with nonempty $A_i \leq v'$. This means that there is a tuple with value $v - \epsilon$ on A_i , with ϵ extremely close to 0. While it is true that this situation may lead to a high query cost for our algorithm, we have not seen this behavior in any real-world database for the simple reason that it will make it extremely difficult for a normal user of the hidden database to specify a query that unveils the tuple with $A_i = v - \epsilon$.

Algorithm 1 SQ-DB-SKY

```

1: QueryQ = {SELECT * FROM D};    S = {}
2: while QueryQ is not empty
3:   q = QueryQ.dequeue();    T = Top-k(q)
4:   if T is not empty
5:     Append the none-dominated tuples in T to S
6:   if T contains k tuples
7:     Construct m queries q1, ..., qm where query qi appends
8:     predicate "Ai < T0[Ai]" to q
9:     Append q1, ..., qm to QueryQ

```

3.2 Query-Cost Analysis

Algorithm SQ-DB-SKY has one nice property and one problem in terms of query cost: The nice property is that the top-1 tuple returned by every node (i.e., query) must be on the skyline (because it cannot be dominated by a tuple not matching the query). The problem, however, is that a skyline tuple t might be returned as No. 1 by *multiple* nodes, potentially leading to a large tree size and thus a high query cost. For example, if t has $t[A_1] < t_1[A_1]$ and $t[A_2] < t_2[A_2]$, then it might be returned by both q_2 and q_3 .

Worst-Case Analysis: Given the overlap between tuples returned by different nodes, the key for analyzing the query cost of SQ-DB-SKY is to count how many nodes in the tree return a tuple. Because we are analyzing the worst-case scenario, we have to consider $k = 1$ and any arbitrary, ill-behaved, system ranking functions. In other words, so long as a tuple matches a node, it may be returned by it. To this end, there is almost no limit on how many times a tuple can be returned, except the following *prefix-free* rule:

Note that each node in the tree can be (uniquely) represented by a sequence of 2-tuples $\langle t_i, A_j \rangle$, where t_i is a skyline tuple returned by a node, and A_j is an attribute corresponding to the branch taken from the node. For example, the nodes corresponding to q_2 and q_3 are represented as $\langle t_1, A_1 \rangle$ and $\langle t_1, A_1 \rangle, \langle t_2, A_1 \rangle$, respectively. The one property that all nodes returning the same tuple t must satisfy is that the sequence representing one node, say q , *cannot be a prefix* of the sequence representing another, say q' . The reason is simple: if the sequence of q is a prefix of q' , then q' must be in the subtree of q . However, according to the design of SQ-DB-SKY, since q returns t , none of the nodes in the subtree of q matches t . This contradicts the assumption that both q and q' return t .

Given the prefix-free rule, a crude upper bound for the number of nodes returning a tuple is $w \leq |S|^m$, where $|S|$ is the num-

ber of skyline tuples. This is because a query can have at most m predicates, each with a different attribute and a value (i.e., v as in $A_i < v$) equal to that of one of the skyline tuples (i.e., $v = t[A_i]$ where t is a skyline tuple). Since no query of concern can be the prefix of another, the maximum number of such queries is $O(|S|^m)$. Given this bound, the maximum number of nodes in the tree is $O(|S| \cdot (|S|^m) \cdot (m + 1)) = O(m \cdot |S|^{m+1})$.

One can make two observations from this worst-case bound: First, the query cost of SQ-DB-SKY depends on the number of skyline tuples, not the total number of tuples. This is good news because, as prior research on skyline sizes [6] shows, the number of skyline tuples is likely orders of magnitude smaller than the number of tuples. Another observation, however, is seemingly bad news: the worst-case cost grows exponentially with the number of attributes m . Fortunately, this is mostly the artifact of an arbitrary system ranking function we must assume in the worst-case analysis, rather than an indication of what happens in practice. To understand why, consider what really happens when the worst-case result strikes, i.e., a tuple t is returned by queries with $\Omega(m)$ predicates.

Consider a Level- m node returning t . Let its 2-tuple sequence be $\langle t_1, A_1 \rangle, \dots, \langle t_m, A_m \rangle$. What this means is not only that t outperforms t_i on A_i for all $i \in [1, m]$, but also that t_m does the same (i.e., outperforms t_i on A_i) for all $i \in [1, m - 1]$, t_{m-1} for all $i \in [1, m - 2]$, etc. In other words, this tuple t is likely ranked highly on many attributes - yet its overall rank is too low to be returned by any of the m predecessor queries. While this could occur for an ill-behaved system ranking function, it is difficult to imagine a reasonable ranking function doing the same. As we show as follows, so long as we assume a "reasonable" ranking function, the worst-case query cost can indeed be reduced by orders of magnitude, no matter what the underlying data distribution is.

Average-Case Analysis: By "average-case" analysis, we mean an analysis done based on a single assumption: the system ranking function is *random among skyline tuples* - i.e., for any query q , the ranking function returns a tuple chosen uniformly at random from $S(q)$, i.e., the set of skyline tuples matching q . One can see that this represents the "average" case as a randomly chosen skyline tuple from $S(q)$ can be considered an average of the top-1 selections of all legitimate ranking functions given q and the database D . As we shall discuss after this analysis, this is likely still "worse" than what happens in practice. Yet even this conservatism assumption is enough to significantly reduce the worst-case query cost.

The most important observation for our average-case analysis can be stated as follows: The expected query cost (taken over the aforementioned randomness of the system ranking function) of SQ-DB-SKY is a *deterministic function* of the number of skyline points $|S|$, regardless of how the tuple are actually distributed.

To understand why, we start from the simplest case of $|S| = 1$. In this case, the SELECT * query returns the single skyline tuple, while the m branches of it all return empty, finishing the algorithm execution. In other words, the query cost is always $C_1 = m + 1$ (where the subscript 1 stands for $|S| = 1$). Now consider $|S| = 2$. Here, depending on which tuple is returned by SELECT *, some of its m branches may be empty; while some others may return the other skyline tuple. Let m_0 be the number of empty branches. For the $(m - m_0)$ non-empty branches, we essentially need C_1 queries to examine each and its m sub-branches (all of which will return empty). One can see that the overall query cost will be

$$C_2 = 1 + m_0 + (m - m_0) \cdot C_1. \quad (1)$$

Interestingly, regardless of how tuples are distributed, the above-described random ranking always yields $E(m_0) = m/2$ and thus

$$E(C_2) = 1 + m/2 + C_1 \cdot m/2, \quad (2)$$




Figure 1: SQ-DB-SKY Tree illustration

	A1	A2	A3
t1	5	1	9
t2	4	4	8
t3	1	3	7
t4	3	2	3

Figure 2: Illustration of example




Figure 3: SQ-DB-SKY example tree




Figure 4: RQ-DB-SKY example tree

where the expected value $E(\cdot)$ is taken over the randomness of the ranking function. To see why, note that m_0 is indeed the number of attributes on which the tuple returned by SELECT^* outperforms the other tuple in the database. Since the ranking function chooses the returned tuple uniformly at random, the expected value of m_0 is always $m/2$ regardless of what the actual values are.

Similarly when $|S| > 2$, $C_s = 1 + m_0 + m_1 \cdot C_1 + \dots + m_{s-1} \cdot C_{s-1}$, where m_i is the number of attributes on which i skyline tuples outrank the tuple returned by SELECT^* (t_0). Since the probability that t_0 is outranked by i skyline tuples on a given attribute is $1/s$, the expected number of such attributes is m/s . Consequently, the expected query cost of SQ-DB-SKY is

$$E(C_s) = 1 + \frac{m}{s} \cdot \sum_{i=0}^{s-1} E(C_i) \quad (3)$$

where $C_0 = 1$. With Z-transform and differential equations,

$$E(C_s) = \frac{m((m+s-1)! - (m-1)!s!)}{(m-1)(m-1)!s!}. \quad (4)$$

For example, when $m = 2$, we have $E(C_s) = 2s$.

We now show why this average-case query cost is orders of magnitude smaller than the worst-case result. First, since $E(C_i) \geq m+1$ for all $i \geq 1$, we can derive from (3) that

$$E(C_s) \leq \frac{m+1}{m} \cdot \frac{m}{s} \cdot \sum_{i=0}^{s-1} E(C_i) = \frac{m+1}{s} \cdot \sum_{i=0}^{s-1} E(C_i) \quad (5)$$

Clearly, if we set F_i such that $F_0 = 1$ and $F_s = ((m+1)/s) \cdot \sum_{i=0}^{s-1} F_i$, then we have $E(C_i) \leq F_i$ for all $i \geq 0$. Consider the ratio between F_s and F_{s-1} when $s \gg m$. Note that $F_{s-1} = (m+1)/(s-1) \cdot \sum_{i=1}^{s-2} F_i$ - i.e.,

$$\sum_{i=1}^{s-1} F_i = \frac{s+m}{m+1} \cdot F_{s-1}. \quad (6)$$

In other words,


$$E(C_s) \leq F_s = \frac{m+1}{s} \cdot \frac{s+m}{m+1} \cdot F_{s-1} = \frac{s+m}{s} F_{s-1} \quad (7)$$

$$= \frac{(s+m)!}{s! \cdot m!} = \binom{s+m}{m} \quad (8)$$


$$\leq \left(\frac{(s+m) \cdot e}{m} \right)^m = \left(e + \frac{e \cdot s}{m} \right)^m \quad (9)$$

One can see that the growth rate of F_s (with $|S|$) is much slower than what is indicated by the worst-case analysis. Figure 5 confirms this finding by showing the average and worst-case cost of SQ-DB-SKY for the cases where $m = 4$ and $m = 8$.

Before concluding the average case analysis, we would like to point out that even this analysis is likely an overly conservative one. To understand why, note from (1) that the smaller m_0 is, i.e.,



(a) m=4



(b) m=8

Figure 5: Comparing worst and average cost of SQ-DB-SKY

the more branches return empty, the smaller the query cost will be. In the average-case analysis, since we assume a random order of skyline tuples, $E(m_0) = m/|S|$, i.e., the top-ranked tuple returned by SELECT^* features the top-ranked value on an average of $m/|S|$ attributes. Clearly, with a real-world ranking function, this number is likely to be much higher, simply because the more “top” attributes values a tuple has, the more likely a reasonable ranking function would rank the tuple at the top. As a result, the query cost in practice is usually even lower than what the average-case analysis suggests, as we show in the experimental results.

4. SKYLINE DISCOVERY FOR RQ-DB

We now consider the RQ-DB case where range queries support two-ended ranges, rather than one-ended as in the SQ-DB case. Since RQ-DB has a more powerful interface, a straightforward solution here is to directly use Algorithm SQ-DB-SKY. One can see that the algorithm still guarantees complete skyline discovery.

The problem with this solution, however, lies in cases where $|S|$, the number of skyline tuples, is large. Specifically, when $|S|$ approaches the database size n , the worst-case query cost may actually be larger than the baseline query cost of $O(m \cdot n)$ for crawling the entire database over a RQ-DB interface [23]. This indicates what SQ-DB-SKY fails to (or cannot, as it was designed for SQ-DB) leverage - i.e., the availability of both ends on range queries - may reduce the query cost significantly when $|S|$ is large. We consider how to leverage this opportunity in this section.

4.1 Key Idea: Algorithm RQ-DB-SKY

A Simple Revision and Its Problem: Our first idea for reducing the query cost stems from a simple observation on the design of q_2 to q_4 described above: Instead of having them as three overlapping queries, we can revise them to be mutually exclusive:

$$\begin{aligned} q_2: & \text{WHERE } A_1 < t_1[A_1] \\ q_3: & \text{WHERE } A_1 \geq t_1[A_1] \ \& \ A_2 < t_1[A_2] \\ q_4: & \text{WHERE } A_1 \geq t_1[A_1] \ \& \ A_2 \geq t_1[A_2] \ \& \ A_3 < t_1[A_3] \end{aligned}$$

With this new design, all m branches from a node in the tree (Figure 1) represent mutually exclusive queries. Interestingly, the completeness of skyline discovery is not affected! For example, any skyline tuple other than t_1 belongs to at least one of q_2 to q_4 .

The effectiveness of this revision is evident from one key observation - because of the mutual exclusiveness and the (still valid) completeness of skyline discovery, now every skyline tuple is returned by *exactly* one node in the tree. While this seemingly solves all the problems in the query-cost analysis for SQ-DB-SKY, it unfortunately introduces another challenge:

Unlike in SQ-DB-SKY where the top-1 tuple returned by every node is a skyline tuple, with this revised tree, a node might return a tuple *not* on the skyline as the No. 1. This can be readily observed from the design of q_2 and q_3 : it is now possible for a tuple returned by q_3 to be dominated by q_2 - as the space covered by q_3 now excludes the space of q_2 . Because of this new problem, the worst-case query cost for this revised algorithm becomes $O(n \cdot m)$, as it is now possible for each of the n tuples in the database (even those not on the skyline) to be returned by a interior node in the tree. While this bound may still be smaller than that of SQ-DB-SKY when $|S|$ approaches n , it may also be much worse when $|S|$ is small. Since we do not have any prior knowledge of $|S|$ before running the algorithm, we need a solution that adapts to the different $|S|$ and offers a consistently small query cost in all cases.

Algorithm RQ-DB-SKY: To achieve this, our key idea is to combine SQ-DB-SKY with the above-described revision to be the more efficient of the two. To understand the idea, note a 1-1 correspondence between the tree constructed in SQ-DB-SKY and the revised tree: In the revised tree, we map every query q in the tree of SQ-DB-SKY to a query $R(q)$ covering all value combinations matching q but not any q' in SQ-DB-SKY which appears before q in the (depth-first) post-order traversal of the tree. Based on this 1-1 mapping, RQ-DB-SKY works as follows.

We traverse the tree in SQ-DB-SKY and issue queries in depth-first preorder. A key additional step here is that, for each query q in the tree, before issuing it, we first check all tuples returned by previously issued queries and check if any of these tuples match q . If none of them does, then we proceed with issuing q and continuing on with the traversal process.

Otherwise, if at least one previously retrieved tuple matches q , then instead of issuing q , we issue its *counterpart* $R(q)$. If $R(q)$ is empty, no new skyline tuple can be discovered from the subtree of q . Thus, we should abandon this subtree and move on. If $R(q)$ returns as No. 1 a tuple t , then either t is dominated by a previously retrieved (skyline) tuple, or it must be a (new) skyline tuple itself. Either way, we must have never seen t before in the answers to the issued queries. If t is dominated by a previously retrieved tuple, say t' , then we generate the children of q according to t' . Otherwise, we generate them according to t . In either case, we continue on with exploring the subtree of q in depth-first preorder. Algorithm 2 depicts the pseudocode of RQ-DB-SKY.

Algorithm 2 RQ-DB-SKY

```

1:  $S = \{\}; \text{ Seen} = \{\}$ 
2: traverse the SQ-DB-SKY tree in depth first preorder and at
   each  $q$  in the tree
3:   if  $\nexists t \in \text{Seen}$  that matches  $q$ 
4:      $T = \text{Top-}k(q)$ 
5:     if  $T$  contains  $k$  tuples
6:       generate the children of  $q$  based on  $T_0$ 
7:   else
8:      $T = \text{Top-}k(R(q))$ 
9:     if  $T$  contains  $k$  tuples
10:      if  $\exists t' \in S$  that dominates  $T_0$ 
11:        generate the children of  $q$  based on  $t'$ 
12:      else, generate the children of  $q$  based on  $T_0$ 
13:   Update  $S$  by  $T$ ;  $\text{Seen} = \text{Seen} \cup T$ 

```




Figure 6: simulation results for RQ-DB-SKY, in comparison with SQ-DB-SKY

THEOREM 3. *Algorithm RQ-DB-SKY is guaranteed to discover all skyline tuples.*

PROOF. The proof can be constructed in analogy to that of Theorem 2. The only difference is that, unlike in the proof for SQ-DB-SKY where t might match more than one of the m branches of a node, here t must match *exactly* one of the m branches, simply because these m branches are mutually exclusive by design in RQ-DB-SKY. Despite of this difference, the logic of the proof stays exactly the same: there must be exactly one branch of the root satisfying t because otherwise t would be dominated by the tuple returned by the root. Recursively, we can construct a path from the root to a leaf node in the tree, such that t satisfies each and every node on the path. Since every leaf node of the tree is a valid or underflowing query, this means that the leaf node must return t , contradicting the assumption that t is not discovered. \square

Once again, let us consider the dummy example provided in Figure 2, and its corresponding RQ-DB-SKY tree in Figure 4. One can see that applying $R(q_4) = \text{WHERE } A_2 \geq 3 \text{ AND } A_3 < 7$, instead of q_4 , causes that each skyline tuple appears in exactly one of the branches.

4.2 Query-Cost Analysis

The key to the query-cost analysis of RQ-DB-SKY is to count the number of internal, i.e., interior, nodes of the tree. There are two important observations: First, the SQ-query q of a interior node must match at least one skyline tuple, as otherwise it would have to return empty which makes the node a leaf. Second, if a interior node is not the first (according to preorder) which returns the skyline tuple, then the node's RQ-query (i.e., $R(q)$) must return a unique tuple in the database that does not match any node accessed before it, because otherwise the node would return empty and become a leaf. With these two observations, an upper bound on the number of internal nodes is $\min(|S|^{m+1}, n)$. As a result, the total query cost of RQ-DB-SKY is $O(m \cdot \min(|S|^{m+1}, n))$.

One might wonder if, for RQ-DB-SKY, we can derive a similar result to the average-case analysis of SQ-DB-SKY which is oblivious to the data distribution. Unfortunately, the query cost of RQ-DB-SKY is data-dependent. The reason is simple: the query cost of RQ-DB-SKY is essentially determined by how many non-skyline tuples match and are returned by the RQ-queries $R(q)$. This number, however, depends on the data distribution: e.g., if all non-skyline tuples are dominated by the skyline tuple returned by SELECT *, then the query cost of RQ-DB-SKY can be extremely small ($\leq m \cdot |S|$). Meanwhile, if very few non-skyline tuples are dominated by skyline tuples returned from nodes at the top of the tree, then RQ-DB-SKY requires many more queries.

Because of the data-dependent nature of RQ-DB-SKY's query cost, to demonstrate the power of its early-termination idea, we resort to the numeric simulations conducted in Section 3. Figure 6 depicts how the query costs of SQ- and RQ-DB-SKY change with the percentage of tuples on the skyline (when the database contains 2000 tuples each with 2 Boolean i.i.d. uniform-distribution




Figure 7: Pruning, R_1 , R_2 , & demo of algorithm execution

attributes). Note that we control the percentage of skyline tuples by adjusting the correlation between the two attributes, where positive correlation leads to fewer skyline tuples. Interestingly, one can observe from the figure that while the performance of RQ- and SQ- do not differ much when $|S|$ is small, RQ- has a much smaller query cost when $|S|$ is large - consistent with the theoretical analysis.

5. SKYLINE DISCOVERY FOR PQ-DB

We now turn our attention point-query PQ-predicates. We first discuss the 2D case (i.e., a database with two attributes) and present an instance-optimal solution PQ-2D-SKY. Then, after pointing out the key differences between 2D and higher dimensional cases, we present Algorithm PQ-DB-SKY, which discovers all skyline tuples from a higher dimensional database by calling (a variation of) PQ-2D-SKY as a subroutine.

5.1 2D Case

Design of Algorithm PQ-2D-SKY: We start with $\text{SELECT } *$ which is guaranteed to return a skyline tuple, say (x_1, y_1) . As shown in Figure 7, we can now prune the 2D search space (for skyline tuples) into two disconnected subspaces, both rectangles. One has diagonals $(0, y_{\max})$ and (x_1, y_1) , while the other has (x_1, y_1) and $(x_{\max}, 0)$, where x_{\max} and y_{\max} are the maximum values for x and y , respectively. We do not need to explore the rectangle with diagonals $(0, 0)$ and (x_1, y_1) because there is no tuple in it (as otherwise it would dominate (x_1, y_1)). We do not need to explore the rectangle with diagonals (x_1, y_1) and (x_{\max}, y_{\max}) either because all tuples in it must be dominated by (x_1, y_1) .

From this point forward, our goal becomes to discover skyline tuples by issuing 1D queries - i.e., queries of the form of either $x = x_0$ or $y = y_0$. An important observation here is that any 1D query we issue will “affect” (precise definition to follow) exactly *one* of the two above-described subspaces. For example, if $x_0 > x_1$, query $x = x_0$ affects only R_2 in Figure 7: It either proves part of the rectangle to be empty (when the query returns empty or a tuple with $y > y_1$), or returns a tuple in the second rectangle that dominates all other tuples with $x = x_0$. In either case, Rectangle R_1 remains the same and still needs to be explored. As another example, if $y_0 > y_1$, then query $y = y_0$ affects only R_1 .

This observation actually leads to a simple algorithm that is guaranteed to be optimal in terms of query cost: at any time, pick one of the remaining (rectangle) subspaces to explore. Let the diagonal points of the subspace be (x_L, y_T) and (x_R, y_B) , where $x_L \leq x_R$ and $y_T \geq y_B$. If $x_R - x_L < y_T - y_B$, then we issue query $x = x_L$. Otherwise, we issue $y = y_B$. For example, in Figure 7, if $x_{\max} - x_1 > y_1$, we issue $y = 0$.

Note the implications of the query answer on the remaining subspace to search: Consider query $q: x = x_L$ as an example. If q returns empty, then the subspace is shrunk to between $(x_L + 1, y_T)$ and (x_R, y_B) . Otherwise, if q returns (x_L, y_2) , then the subspace is shrunk to between $(x_L + 1, y_2)$ and (x_R, y_B) . Either way, the subspace becomes smaller and remains disjoint from other remaining subspace(s). For example, in Figure 7, if $y = 0$ is empty, R_2 is shrunk to between (x_1, y_1) and $(x_{\max}, 1)$. Otherwise, if it returns $(x_2, 0)$, then the subspace is now between (x_1, y_1) and $(x_2, 1)$.

What we do next is to simply repeat the above process, i.e., pick a subspace, determine whether the width or height is larger, and issue the corresponding query. This continues until no subspace remains. Algorithm 3 depicts the pseudo code for PQ-2D-SKY.

Algorithm 3 PQ-2D-SKY

- 1: $T = \text{Top-}k(\text{SELECT } * \text{ FROM } D)$; $S = \{T_0\}$
- 2: Partition search space into rectangles R_1 and R_2 based on T_0
- 3: **while** search space is not fully explored
- 4: Pick a rectangle and identify point query q to issue
- 5: $T = \text{Top-}k(q)$; $S = S \cup T_0$
- 6: **if** T contains k tuples, prune search space based on T_0

Instance Optimality Proof: We now prove the instance optimality of PQ-2D-SKY, i.e., for any given database, there is no other algorithm that can use fewer queries to discover all skyline tuples and *prove* that all skyline tuples have been discovered. Note that the latter requirement (i.e., proof of completeness) is important. To see why, consider an algorithm that issues $\text{SELECT } *$ and then stops. For a specific database that contains only one skyline tuple, this algorithm indeed finds all skyline tuples extremely efficiently. But it is not a valid solution because it cannot guarantee the completeness of skyline discovery.

We prove the instance optimality of PQ-2D-SKY by contradiction: Suppose there exists an algorithm \mathcal{A} , requiring fewer queries. Consider the (rectangle) subspace between (x_L, y_T) and (x_R, y_B) . If $x_R - x_L < y_T - y_B$ yet \mathcal{A} does *not* issue $x = x_L$, then the only alternative is to issue queries $y = y_B, y_B + 1, \dots, y_c$, where y_c is the y -coordinate value of the tuple returned by $x = x_L$ or, in the case where $x = x_L$ returns empty, $y_c = y_T$. An example of this is illustrated in Figure 7: Suppose $y_{\max} - y_1 > x_1$. If \mathcal{A} does not issue $x = 0$, then it must issue $y = y_1, y_2, \dots, y_c$. This is because, in order to guarantee the completeness of skyline discovery, one must “prove” the emptiness of points $(x_L, y_B), (x_L, y_B + 1), \dots, (x_L, y_c - 1)$, (resp. $(x_0, y_1), \dots, (x_0, y_c - 1)$ in Figure 7) while retrieving tuple (x_L, y_c) (resp. (x_0, y_c) in Figure 7). Given that $x = x_L$ is not issued, the only feasible solution is to issue the above-described $y = y_i$ queries.

Yet this contradicts the optimality of Algorithm \mathcal{A} . To understand why, consider two cases respectively: First is when $x = x_L$ returns empty. In this case, \mathcal{A} calls for $y_T - y_B + 1$ queries to be issued, while PQ-2D-SKY issues at most $x_R - x_L$ queries. Since $x_R - x_L < y_T - y_B$, \mathcal{A} is actually worse. Now consider the second case, where $x = x_L$ does return a tuple (x_L, y_c) . In this case, \mathcal{A} calls for c queries to be issued. We also require at most c queries, as $y = y_c$ is no longer needed given the answer to $x = x_L$. This again contradicts the superiority of \mathcal{A} .

Query Cost Analysis: Having established the instance optimality of PQ-2D-SKY, we now analyze exactly how many queries it needs to issue. Let A_1 and A_2 be the two attributes and $t_1, \dots, t_{|S|}$ be the skyline tuples in the database. Without loss of generality, suppose t_i is sorted in the increasing order of A_1 , i.e., $t_i[A_1] \leq t_{i+1}[A_1]$. Note that, since t_i are all skyline tuples, correspondingly there must be $t_i[A_2] \geq t_{i+1}[A_2]$. Denote as t_0 and $t_{|S|+1}$ the two diagonal points of the domain, i.e., $t_0 = \langle 0, \max(\text{Dom}(A_2)) \rangle$ and $t_{|S|+1} = \langle \max(\text{Dom}(A_1)), 0 \rangle$. One can see from the design of PQ-2D-SKY that its query cost is simply

$$C = \sum_{i=0}^{|S|} \min(t_{i+1}[A_1] - t_i[A_1], t_i[A_2] - t_{i+1}[A_2]). \quad (10)$$

Immediately, following Equation 10, a few upper bounds on C are: e.g., $C \leq t_1[A_2]$, $C \leq t_{|S|}[A_1]$, and $C \leq \min_{i \in [1, |S|]} (t_i[A_1] + t_i[A_2])$. These upper bounds indicate a likely small query

cost in practice. To understand why, recall that most web interfaces only present a ranking attribute as PQ when it has a small domain. In addition, it is highly unlikely for such an attribute to have empty domain values - i.e., $v \in \text{Dom}(A_i)$ that is not taken by any tuple in the database - because otherwise users of the PQ interface would be frustrated by the empty result returned after selecting $A_i = v$. When every value in $\text{Dom}(A_1)$ and $\text{Dom}(A_2)$ is occupied, unless the number of skyline tuples is very large, $t_i[A_j]$ is likely small for t_i to be on the skyline, leading to a small query cost in practice. We verify this finding through experimental results in Section 7.

5.2 Algorithm PQ-DB-SKY

Overview: Somewhat surprisingly, the problem changes drastically when dimensionality increases to $m = 3$. This forms a sharp contrast with the SQ/RQ cases where the design of skyline discovery has nothing to do with m , as shown in Section 3 and Section 4.

Specifically, we found a negative result that, unlike in the 2D case, instance optimality becomes provably unachievable when $m \geq 3$. In addition, even discovering all skylines in a 2D subspace of a higher-D database requires a slight revision to PQ-2D-SKY, which we name PQ-2DSUB-SKY. Due to space limitations, please refer to [2] for details the negative-result proof and the design of PQ-2DSUB-SKY. In the following discussions, we provide the pseudocode for PQ-2DSUB-SKY that is then used as a subroutine to construct Algorithm PQ-DB-SKY, our generic algorithm for skyline discovery over point-query interfaces.

Algorithm 4 PQ-2DSUB-SKY

- 1: Assuming that A_1 and A_2 create the current subspace \mathcal{S}
 - 2: **foreach** query q that contains \mathcal{S} and tuple t discovered by q
 - 3: **if** $\forall i > 2, t[A_i] \geq \mathcal{S}[A_i]$
 - 4: Remove the rectangle $(0,0)$ and $(t[A_1], t[A_2])$ from \mathcal{S}
 - 5: **foreach** discovered tuple t that $\forall i > 2, t[A_i] \leq \mathcal{S}[A_i]$
 - 6: Remove the rectangle corresponding to $A_1 \geq t[A_1]$ and $A_2 \geq t[A_2]$ from \mathcal{S}
 - 7: **while** \mathcal{S} is not completely pruned
 - 8: Remove the pruned rows and columns
 - 9: Construct the “block-diagonal” rectangles (\mathcal{R}) between adjacent “lower-bound” skyline points in the subspace
 - 10: Apply PQ-2D-SKY on a rectangle r in \mathcal{R} that agrees with the overall pruned subspace on the dimension to follow
-

Design and Analysis of PQ-DB-SKY: Our proposed technique for higher-dimensional skyline discovery has a key step of applying the application of this algorithm over each 2D subspace of a higher-dimensional space.

Algorithm 5 PQ-DB-SKY

- 1: $T = \text{Top-}k(\text{SELECT } * \text{ FROM } D)$; $S = \{T_0\}$
 - 2: Prune search space based on T_0
 - 3: **while** search space is not fully explored
 - 4: Pick the 2D subspace spanning 2 attributes with largest domain sizes
 - 5: Identify skyline tuples on subspace using PQ-2DSUB-SKY
-

As discussed above, instance optimality is lost once the dimensionality reaches 3. A key reason for this is because one does not know which dimension to “crawl first”, i.e., how to partition a higher-D space into 2D subspaces (e.g., along x , y or z ?). Fortunately, heuristics for dimension selection are easy to identify. The most important factor here is the domain size. To understand why, note that the domain sizes for the two dimensions selected into the 2D subspace have an *additive* effect on query cost, while the others have a *multiplicative* effect. Thus, generally, we should choose the two attributes with the largest domain sizes as the 2D subspace.

Based on the heuristics, the pseudo code of PQ-DB-SKY is depicted in Algorithm 5. Given the exponential nature of dividing a higher-D space into 2D subspaces, the worst-case query cost grows exponentially with the number of attributes. Nonetheless, as argued in the 2D case, the small domain sizes and the value-occupancy property usually lead to a much smaller query cost in practice. Such an effect is likely amplified even further in higher-D cases, as we shall show in the experimental results in Section 7, because of the aforementioned heuristics which places the largest domain-sized attributes in the 2D subspace, leaving the other (multiplicative) attributes with even smaller domains.

6. SKYLINE DISCOVERY FOR MIXED-DB

6.1 Overview

When the hidden database features a mixture of range- and point-predicates, a straightforward idea appears to be applying RQ-DB-SKY directly over the range-predicate attributes and not using the point ones at all (by setting them to $*$), because RQ-DB-SKY is significantly more efficient than PQ-DB-SKY. The problem, however, is that doing so misses skyline tuples, as shown below.

First, note that by setting $A_i = *$ on all point-predicate attributes, the skyline tuples discovered by applying RQ-DB-SKY must indeed be skyline tuples. The problem here, however, is that the completeness proof no longer holds because a skyline tuple might be dominated by another tuple on all range-predicate attributes. Such a tuple will be missed by RQ-DB-SKY. Fortunately, the missing tuples must share a common property which we refer to as the *range-domination property*: every tuple t missed here must be dominated by an already-discovered skyline tuple, say $D(t)$, on all range attributes. Meanwhile, t must surpass $D(t)$ on at least one of the point attributes.

Range-domination is an interesting property because it significantly shrinks the search space for finding the remaining skyline tuples. Consider a simple example where the execution of RQ-DB-SKY returns only one tuple t_0 . In this case, we can define our new search space (for all missing skyline tuples) by simply constructing a conjunctive query with predicates $A_i \geq t_0[A_i]$ for every range-predicate attribute A_i . Depending on the value of t_0 and the data distribution, these conjunctive predicates may significantly reduce the space we must search through with PQ-DB-SKY.

When the range attributes only support one-ended ranges, the above search-space-pruning idea does not work because predicates like $A_i \geq t_0[A_i]$ are not supported. Nonetheless, it is still possible to prune the search space because, in order for a missing tuple to be on the skyline, it must dominate an already discovered tuple on at least one point-predicate attribute. In other words, in the execution of PQ-DB-SKY, we no longer need to consider value combinations of point-predicate attributes that are dominated by all discovered tuples. While this idea has a much weaker pruning power than the above one, it works for the case of two-ended ranges as well, and can be readily integrated with the above idea.

6.2 Details for Leveraging Two-Ended Ranges

Before presenting our final MQ-DB-SKY algorithm, an important issue remains on how exactly to leverage the above-described RQ-based search-space pruning. A straightforward method is to construct for each discovered skyline tuple t_i the above-described subspace defined by conjunctive predicates $A_i \geq t_i[A_i]$, and then run PQ-DB-SKY over the space. The problem, however, is that PQ-DB-SKY cannot be directly used in this case because its 2D-subspace-discovery subroutine relies on an important property: if a tuple matches but is not returned by a 1D query q_0 as the No. 1

tuple, then it cannot be on the skyline. Unfortunately, this property no longer holds in the mixed case.

To address this problem, we devise a new subroutine MIXED-DB-SKY as follows. For each skyline tuple t_0 discovered by the range-query algorithm, let predicate $P(t_0)$ be $(t[A_1] \geq t_0[A_1]) \& \dots \& (t[A_h] \geq t_0[A_h])$ for all range attributes A_1, \dots, A_h . For each point attribute $B_i (i \in [1, g])$ and each value $v < t_0[B_i]$, we construct a query q : WHERE $P(t_0) \& (t[B_i] = v)$.

If this query returns empty, we move on to the next query. The premise (of the efficient execution of this algorithm) is that, in practice, most such queries q will return empty, quickly pruning the remaining search space. If q returns at least one tuple, we need to start crawling the subspace defined by q . Now recall our PQ-DB-SKY algorithm for point-query skyline discovery. Our first step over there is to “partition” the space into 2-dimensional subspaces (i.e., by enumerating all possible value combinations for the other $g - 2$ attributes, where g is the number of point attributes) and deal with them one after another. This step remains the same. Specifically, at any point we have an empty answer, we can stop further partitioning the current subspace. When we go all the way to a 2-dimensional subspace (without being stopped by an empty answer) then we’ll have to crawl the entire 2D plane to find all tuples in it, instead of using the “2D skyline discovery” approach in PQ-DB-SKY. This is the only difference with MIXED-DB-SKY.

A concern with this design is the large number of times MIXED-DB-SKY may have to be called to completely discover the skyline. Note that a *single* call of MIXED-DB-SKY without any appended predicates is sufficient to unveil all skyline tuples. Yet when we append the range predicates to prune the search space, the repeated executions of MIXED-DB-SKY, especially many skyline tuples are discovered by RQ-DB-SKY, may lead to an even higher query cost.

To address this problem, we consider a slightly different solution of maintaining a single execution of MIXED-DB-SKY. This time, instead of designing m_{TE} conjunctive predicates for each of the discovered skyline tuples, we do so only once for the *union* of (dominated) data spaces corresponding to all of them. Specifically, for each two-ended range attribute A_j , its corresponding (appended) predicate is now

$$A_j \geq \min(t_1[A_j], \dots, t_h[A_j]), \quad (11)$$

where t_1, \dots, t_h are the initially-discovered skyline tuples. One can see that these predicates ensure comprehensiveness of skyline discovery, as any tuple that fails to satisfy (11) must not be dominated by any discovered tuple on the range-predicate attributes - in other words, this tuple must have already been discovered by RQ-DB-SKY. On the other hand, given the (relatively) small number of skyline tuples, $\min(t_1[A_j], \dots, t_h[A_j])$ may still have substantial pruning power, yet reducing the number of executions of MIXED-DB-SKY to exactly 1.

6.3 Algorithm MQ-DB-SKY

We now combine all the above ideas to produce our ultimate (most generic) algorithm, MQ-DB-SKY, which supports any arbitrary combination of two-ended range, one-ended range, and point predicate attributes. Note that when there are two-ended range attributes in the database, we use the pruning idea discussed in the above subsection. When there are only one-ended range attributes besides point ones, our algorithm is limited to using the weaker pruning idea discussed in Section 3. If there are only one-ended range, two-ended range, or point-predicate attributes in the database, MQ-DB-SKY is reduced to SQ-, RQ-, and PQ-DB-SKY, respectively. Finally, if there are a mixture of one-ended and two-ended range-predicate attributes but no point-predicate attribute in

the database, MQ-DB-SKY is reduced to a simple revision of RQ-DB-SKY which leverages the availability of “>” predicates on only attributes that support two-ended ranges.

Algorithm 6 MQ-DB-SKY

- 1: $S = \text{apply RQ-DB-SKY}() \text{ on Range predicates; } P = \text{“”}$
 - 2: **foreach** range attribute $r \in R$
 - 3: append P by “AND $t[r] \geq \min_{\forall t_j \in S} (t_j[r])$ ”
 - 4: **foreach** point attribute B_i and each value $v < \max_{\forall t_j \in S} (t_j[B_i])$
 - 5: q : WHERE P AND $(t[B_i] = v)$
 - 6: $T = \text{Top-}k(q)$; update S by T
 - 7: **if** T contains k tuples
 - 8: partition the space defined q in 2D planes
 - 9: **foreach** plane, crawl the tuples in it and update S
-

7. EXPERIMENTAL EVALUATION

7.1 Experimental Setup

In this section, we present the results of our experiments, all of which were run on real-world data. Specifically, we started by testing a real-world dataset we have already collected. We constructed a top- k web search interface for it and then ran our algorithms through the interface. Since we have full knowledge of the dataset and control over factors such as database size, etc., this dataset enables us to verify the correctness of our algorithms and test their performance over varying characteristics of the database. Then, we tested our algorithms *live online* over three real-world websites, including the largest online diamond and flight search services in the world, echoing the motivating examples discussed in Introduction.

Offline Dataset: The offline dataset we used is the flight on-time database published by the US Department of Transportation (DOT). It records, for all flights conducted by the 14 US carriers in January 2015,² attributes such as scheduled and actual departure time, taxiing time and other detailed delay metrics. The dataset has been widely used by third-party websites to identify the on-time performance of flights, routes, airports, airlines, etc.

The dataset consists of 457,013 tuples over 28 attributes, from which 9 ordinal attributes were used as *ranking attributes*³: *Dep-Delay*, *Taxi-out*, *Taxi-in*, *Actual-elapsed-time*, *Air-time*, *Distance*, *Delay-group-normal*, *Distance-group*, *ArrivalDelay*. The domain of the 9 ranking attributes range from 11 to 4,983. Two of the 9 attributes, *Delay-group-normal* and *Distance-group*, were already discretized by DOT (i.e., “grouped”, according to the dataset description). Thus, we used them as PQ (point-query-predicate) attributes by default. For a few tests which call for more PQ attributes, we also consider four other derived attributes, *Taxi-out group*, *Taxi-in group*, *ArrivalDelay group*, *Air-Time group* as potential PQ. The other attributes were used as range-predicate attributes - whether it is SQ or RQ depends on the specific test setup.

For all attributes, we defined the preferential order so that shorter delay/duration ranks higher than longer values. For non-time attributes, i.e., *Distance* and *Distance-group*, we assigned a higher rank to longer distances than shorter ones, given that the same amount of delay likely impacts short-distance flights more than longer ones. We also tested the case where shorter distances are ranked higher, and found little difference in the performance. To

²from http://www.transtats.bts.gov/DL_SelectFields.asp?Table_ID=236&DB_Short_Name=On-Time

³The others, such as Flight Number, are considered filtering attributes and not used in the experiments.

construct the top- k interface, we also need to define a ranking function it uses. Here we simply used the SUM of attributes for which smaller values are preferred MINUS the SUM of attributes for which larger values are preferred.

Online Experiments: We conducted live experiments over three real-world websites: Blue Nile (BN) diamonds, Google Flights (GF), and Yahoo! Autos (YA).

Blue Nile (BN)⁴ is the largest online retailer of diamonds. At the time of our tests, its database contained 209,666 tuples (diamonds) over 6 attributes: *Shape*, *Price*, *Carat*, *Cut*, *Color*, *Clarity*, the last 5 of which have universally accepted preferential (global) orders, i.e., lower *Price*, higher *Carat*, more precise *Cut*, low trace of *Color* and high *Clarity*. We used these 5 attributes to define skyline tuples. BN offers two-ended range predicates (RQ) on all five attributes, with the default ranking function being *Price* (low to high).

Google Flights (GF) is one of the largest flight search services and offers an interface called QPX API⁵. We consider the scenario of a traveler looking to get away with a one-way flight after a full day of work. We used three filtering attributes, *DepartureCity*, *ArrivalCity* and *DepartureDate*, and four supported ranking attributes: *Stops*, *Price*, *ConnectionDuration*, and *DepartureTime*. Here the traveler likely prefers fewer *Stops*, lower *Price*, shorter *ConnectionDuration*, and later *DepartureTime*. QPX API supports SQ (i.e., single-ended ranges) on *Stops*, *Price*, *ConnectionDuration*, and RQ (i.e., two-ended) on *DepartureTime*. The default ranking function used by GF is price (low to high).

Yahoo! Autos (YA)⁶ offers a popular search service for used cars. In our experiments, we considered those listed for sale within 30 miles of New York City, totaling 125,149 cars. We considered three ranking attributes *Price* (lower preferred), *Mileage* (lower preferred), *Year* (higher preferred), all of which are supported as two-ended ranges (RQ) by YA, and the ranking function of *Price* (low to high).

Algorithms Evaluated: We tested the four main algorithms described in the paper, SQ-, RQ-, PQ-, and MQ-DB-SKY. We also compared their performance with a baseline technique of first crawling all tuples from the hidden web database using the state-of-the-art crawling algorithm in [23], and then extracting the skyline tuples locally. We refer to this technique as BASELINE.

Performance Measures: As we proved theoretically in the paper, all algorithms guarantee complete skyline discovery. We confirmed this in all experiments we ran offline (and have the ground truth for verification). Since precision is not an issue, the key performance measure becomes efficiency which, as we discussed earlier, is the number of queries issued to the web database.

7.2 Experiments over Real-World Dataset

Interfaces with Range Predicates: We started with testing skyline discovery through range-query interfaces, i.e., SQ and RQ, over the DOT dataset. Figure 8 compares the query cost required for complete skyline discovery by RQ-DB-SKY and BASELINE when k (as in top- k offered by the web database) varies from 1 to 50. Note that SQ-DB-SKY is not depicted here because the range-query-based crawling in BASELINE requires two-ended range support. One can observe from the figure that, while both algorithms benefit from a larger k as we predicted, our RQ- algorithm outperforms the baseline by orders of magnitude for all k values. Given the significant performance gap between BASELINE and our solutions, we

skip the BASELINE figure for most of the offline results, before showing it again in the online live experiments.

Figure 9 depicts how the query cost of SQ- and RQ-DB-SKY change when the database size n ranges from 50K to 400K. To test databases with varying sizes, we drew uniform random samples from the DOT dataset. The figure also shows the change of $|S|$, the number of skyline tuples. One can see from the figure that RQ-DB-SKY is more efficient than SQ- because it uses the more powerful, two-ended, search interface. Perhaps more interestingly, neither algorithm's query cost depend much on n . Instead, they appear more dependent on the number of skyline tuples $|S|$ - consistent with our theoretical analysis.

Figure 10 varies the number of attributes m . While both RQ- and SQ- require more queries when there are more attributes, RQ- again consistently outperforms SQ-DB-SKY. Note that the increase on query cost is partially because of the rapid increase of the number of skyline tuples with dimensionality [6]. In any case, the query cost for RQ- and SQ-DB-SKY remain small, compared to the theoretical bounds, even when the dimensionality reaches 10.

Interfaces with Point Predicates: In the next set of experiments, we tested PQ-DB-SKY. Figure 11 shows how its query cost varies with n and m . Interestingly, while the query cost barely changes with n varying from 20,000 to 100,000, it increases significantly when m changes from 3 to 5, just as predicted by our theoretical analysis. In Figure 12, we further tested how the query cost changes with varying domain sizes. To enable this test, for each given domain size (from $v = 5$ to 15), we first select all PQ attributes with domain larger than v , and then remove from the domain of each attribute all but v values (along with their associated tuples). Then, we randomly selected 100,000 tuples from the remaining tuples as our testing database. One can see from the result that, while larger attribute domains do lead to a higher query cost, the increase on query cost is not nearly as fast as the data space (which grows with v^m) - indicating the scalability of PQ-DB-SKY to larger domains.

Interfaces with Mixed Predicates: We next tested a more realistic search interface that contains a mixture of range and point predicates. We started with 3 RQ and 2 PQ predicates and evaluated how the query cost varies with database size. Figure 13 shows that, as expected, the number of tuples only have minimal impact on query cost. We then tested how varying number of RQ and PQ attributes affect our performance. The two lines in Figure 14 represent, respectively, (1) 1 PQ attribute with the number of RQ attributes varying from 2 to 5, and (2) 1 RQ attribute with the number of PQ ones from 2 to 5. One can observe from the figure that the impact on query cost is much more pronounced on an increase of the number of PQ attributes - consistent with earlier discussions in the paper.

Anytime Property of Skyline Discovery: Recall from §1 that all algorithms in the paper feature the anytime property, i.e., one can stop the algorithm execution at any time to return a subset of skyline tuples (over the entire database). Note that BASELINE does not have this feature, as there is no way for it to determine if a tuple is truly on the skyline before the entire database is crawled. Figures 15 and 16 trace the progress of SQ-, RQ- and PQ-DB-SKY over 100,000 tuples (5 predicates in RQ-DB and 4 in PQ-DB case) and demonstrate how the number of discovered skyline tuples changes with query cost.

There are some interesting observations from the two figures. In Figure 15, note that SQ-DB-SKY could find the first 16 skylines without facing a skyline twice, leading to identical performance with RQ- up to that point. Afterwards, however, it started getting the same skyline tuple multiple times, leading to poorer performance than RQ-DB-SKY when the number of discovered skyline tuples reaches 23. In Figure 16, note that despite the limitations

⁴<http://www.bluenile.com/diamond-search>

⁵<https://developers.google.com/qp-express/>

⁶<https://autos.yahoo.com/used-cars/>




Figure 8: Range Predicates: Impact of k




Figure 9: Range Predicates: Impact of n




Figure 10: Range Predicates: Impact of m




Figure 11: Point Predicates: Impact of n




Figure 12: Point Predicates: Impact of Domain Size




Figure 13: Mixed Predicates: Impact of n




Figure 14: Mixed Predicates: Varying Range and Point Predicates




Figure 15: Anytime Property of SQ and RQ-DB-SKY

of PQ, our algorithm managed to discover all skyline tuples with fewer than 600 queries. The peak between the 8th and 9th tuples is caused by queries “wasted” for crawling an area that did not contain any skyline tuple.

7.3 Online Demonstration

Skyline Discovery over Blue Nile (BN): For BN, we discovered a total of 2,149 tuples on the skyline. We compared the performance of MQ-DB-SKY with BASELINE ($k = 50$), with the results depicted in Figure 17. Note that we stopped the execution of BASELINE when its query cost reached 10,000 queries, at which time it only managed to discover 1113 skyline tuples⁷. On the other hand, our MQ- algorithm discovers the entire skyline with an average query cost of only 3.5 per skyline tuple.

Skyline Discovery over Google Flights (GF): Our experiment setup was as follows. We randomly chose a pair of airports from the top-25 busiest airports in USA and a date between November 1 and 30, 2015, and sought to find all skyline flights on that day. We repeated this process for 50 different pairs and report the average query cost. The number of skyline flights varied between 4 to 11. Figure 18 shows the results. Note that we did not compare against BASELINE here because GF offers SQ only for attributes such as *Stops*, *Price*, and *ConnectionDuration*, while BASELINE requires two-ended range support for crawling. We verified the correctness of the results by crawling all the flights for the same date and comparing the results. One can observe that our algorithm is highly efficient even when $k = 1$. Specifically, it was able to discover all skyline tuples with query cost below 50, which is the (free) rate limit imposed per user account per day by GF (QPX API).

Skyline Discovery over Yahoo! Autos (YA): For YA, we discovered a total of 1,601 skyline tuples. Figure 19 shows the performance of our MQ- algorithm and the comparison with BASELINE. Here $k = 50$. Once again, we had to discontinue BASELINE at

⁷Note that, as discussed earlier, BASELINE would not be able to output these skyline tuples despite of having discovered them because BASELINE lacks the anytime property.

10,000 queries before it were able to complete crawling. On the other hand, our MQ-DB-SKY algorithm managed to discover the entire skyline with an average query cost below 2 per skyline tuple.

8. RELATED WORK

Crawling and Data Analytics over Hidden Databases: While there has been a number of prior works on crawling, sampling, and aggregate estimation over hidden web databases, there has not been any study on the discovery of skyline tuples over hidden databases. Crawling structured hidden web databases have been studied in [19, 22, 23]. [8–10] describe efficient techniques to obtain random samples from hidden web databases that can then be utilized to perform aggregate estimation. Recent works such as [17, 25] propose more sophisticated sampling techniques that reduce variance of aggregate estimation.

Skyline Computation: Skyline operator was first described in [5] and number of subsequent work have studied it from diverse contexts. [24] and [7] proposed efficient algorithms with the help of indices and pre-sorting respectively. Online and progressive algorithms were described in [14, 20]. The problem of skyline over streams [15], partial orders [3], uncertain data [21], and groups [27] have also been studied. [4, 18] study the problem of retrieving the skyline from multiple web databases that expose a ranked list of all tuples according to a pre-known ranking function. Such special access might not always be available for a third party operator. Our work is the first to study the problem of skyline computation over structured hidden databases by using only the publicly available access channels.

Applications of Skyline Tuples: Skyline tuples have a number of applications in diverse contexts. A skyline tuple is not dominated by another tuple while a K -Skyband tuple is dominated by at most $K - 1$ tuples in the database. The top- k tuples of any monotone aggregate function must belong to K -Skyband where $k \leq K$ [12]. The numerous applications of top- k queries can be found in [13]. Other applications of Skyline include nearest neighbor search, answering the preference queries and finding the convex-hull. Recently, the notion of reverse skyline [11], K -Dominating




Figure 16: Anytime Property of PQ-DB-SKY




Figure 17: Online Experiments: Blue Nile Diamonds




Figure 18: Online Experiments: Google Flights




Figure 19: Online Experiments: Yahoo! Autos

and K -Dominant [26], and top- K representative skylines [16] have been investigated with a number of applications including query re-ranking and product design.

9. FINAL REMARKS

In this paper, we studied an important yet novel problem of skyline discovery over web databases with a top- k interface. We introduced a taxonomy of the search interfaces offered by such a database, based on whether single-ended range, two-ended range, or point predicates are supported. We developed efficient skyline discovery algorithms for each type and combine them to produce a solution that works over a combination of such interfaces. We developed rigorous theoretical analysis for the query cost, and conducted a comprehensive set of experiments on real-world datasets, including a live online experiment on Google Flights, which demonstrate the effectiveness of our proposed techniques.

10. ACKNOWLEDGMENTS

The work of Abolfazl Asudeh, Saravanan Thirumuruganathan and Gautam Das was supported in part by the National Science Foundation under grant 1343976, the Army Research Office under grant W911NF-15-1-0020, and a grant from Microsoft Research. Nan Zhang was supported in part by the National Science Foundation, including under grants 1117297, 1343976, 1443858, and by the Army Research Office under grant W911NF-15-1-0020. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the sponsors listed above.

11. REFERENCES

- [1] B. Arai, G. Das, D. Gunopulos, and N. Koudas. Anytime measures for top- k algorithms. In *VLDB*, 2007.
- [2] A. Asudeh, S. Thirumuruganathan, N. Zhang, and G. Das. Discovering the skyline of web databases. *CoRR*, abs/1512.02138, 2015.
- [3] A. Asudeh, G. Zhang, N. Hassan, C. Li, and G. Zaruba. Crowdsourcing pareto-optimal object finding by pairwise comparisons. *CIKM*, 2015.
- [4] W.-T. Balke, U. Güntzer, and J. X. Zheng. Efficient distributed skylining for web information systems. In *EDBT*, 2004.
- [5] S. Borzsony, D. Kossmann, and K. Stocker. The skyline operator. In *ICDE*, 2001.
- [6] C. Buchta. On the average number of maxima in a set of vectors. *Information Processing Letters*, 33(2), 1989.
- [7] J. Chomicki, P. Godfrey, J. Gryz, and D. Liang. Skyline with presorting. In *ICDE*, 2003.

- [8] A. Dasgupta, G. Das, and H. Mannila. A random walk approach to sampling hidden databases. In *SIGMOD*, 2007.
- [9] A. Dasgupta, N. Zhang, and G. Das. Leveraging count information in sampling hidden databases. In *ICDE*, 2009.
- [10] A. Dasgupta, N. Zhang, and G. Das. Turbo-charging hidden database samplers with overflowing queries and skew reduction. In *EDBT*, 2010.
- [11] E. Dellis and B. Seeger. Efficient computation of reverse skyline queries. In *VLDB*, 2007.
- [12] Z. Gong, G.-Z. Sun, J. Yuan, and Y. Zhong. Efficient top- k query algorithms using k -skyband partition. In *Scalable Information Systems*. Springer, 2009.
- [13] I. F. Ilyas, G. Beskales, and M. A. Soliman. A survey of top- k query processing techniques in relational database systems. *ACM Computing Surveys (CSUR)*, 40(4), 2008.
- [14] D. Kossmann, F. Ramsak, and S. Rost. Shooting stars in the sky: An online algorithm for skyline queries. In *VLDB*, 2002.
- [15] X. Lin, Y. Yuan, W. Wang, and H. Lu. Stabbing the sky: Efficient skyline computation over sliding windows. In *ICDE*, 2005.
- [16] X. Lin, Y. Yuan, Q. Zhang, and Y. Zhang. Selecting stars: The k most representative skyline operator. In *ICDE*, 2007.
- [17] T. Liu, F. Wang, and G. Agrawal. Stratified sampling for data mining on the deep web. *Frontiers of Computer Science*, 6(2):179–196, 2012.
- [18] E. Lo, K. Y. Yip, K.-I. Lin, and D. W. Cheung. Progressive skylining over web-accessible databases. *Data & Knowledge Engineering*, 2006.
- [19] J. Madhavan, D. Ko, L. Kot, V. Ganapathy, A. Rasmussen, and A. Halevy. Google’s deep web crawl. *VLDB*, 2008.
- [20] D. Papadias, Y. Tao, G. Fu, and B. Seeger. An optimal and progressive algorithm for skyline queries. In *SIGMOD*, 2003.
- [21] J. Pei, B. Jiang, X. Lin, and Y. Yuan. Probabilistic skylines on uncertain data. In *VLDB*, 2007.
- [22] S. Raghavan and H. Garcia-Molina. Crawling the hidden web. *VLDB*, 2000.
- [23] C. Sheng, N. Zhang, Y. Tao, and X. Jin. Optimal algorithms for crawling a hidden database in the web. *VLDB*, 2012.
- [24] K.-L. Tan, P.-K. Eng, B. C. Ooi, et al. Efficient progressive skyline computation. In *VLDB*, 2001.
- [25] F. Wang and G. Agrawal. Effective and efficient sampling methods for deep web aggregation queries. In *EDBT*, 2011.
- [26] M. L. Yiu and N. Mamoulis. Efficient processing of top- k dominating queries on multi-dimensional data. In *VLDB*, 2007.
- [27] N. Zhang, C. Li, N. Hassan, S. Rajasekaran, and G. Das. On skyline groups. *TKDE*, 26(4), 2014.